

英制型号 Inch Bearing Model No				内径 ID	外径 OD	法兰盘外径 Flange OD	厚度 Thickness		基本额定动负荷	基本额定静负荷	允许回转数 Speed		钢球 Balls	
							开式厚度	闭式厚度			润滑脂 Grease	润滑剂 Lubri	个数	直径
开式 Open Type	法兰开式 Open Type	防尘盖 ZZ/RS	法兰盘防尘盖 ZZ/RS	d	D	Df	B	B1	Cr(N)	Cor(N)	*1000rpm	Qty	Dw	
R133	FR133	-	-	2.38	4.762	5.944	1.588	-	189	60	80	95	7	0.8
-	-	R133ZZ	FR133ZZ	-	4.762	5.944	-	2.38	144	53	80	95	10	0.6
R1-5	FR1-5	R1-5ZZ	FR1-5ZZ	-	7.938	9.119	2.779	3.571	552	176	60	71	6	1.588
R144J	FR144J	R144JZZ	FR144JZZ	3.175	6.350	7.518	2.38	2.779	311	110	67	80	8	1
R144	FR144	R144ZZ	FR144ZZ	-	6.350	7.518	2.38	2.779	284	96	67	80	7	1
R2-5	FR2-5	R2-5ZZ	FR2-5ZZ	-	7.938	9.119	2.779	3.571	558	180	60	67	6	1.588
R2-6	FR2-6	R2-6ZZ	FR2-6ZZ	-	9.525	10.719	2.779	3.571	640	227	53	63	7	1.588
R2	FR2	R2ZZ	FR2ZZ	-	9.525	11.176	3.967	3.967	631	219	56	67	7	1.588
R2A	-	R2AZZ	-	-	12.700	-	4.366	4.366	640	227	53	63	7	1.588
R155	FR155	R155ZZ	FR155ZZ	3.967	7.938	9.119	2.779	3.175	359	150	53	63	10	1
R156	FR156	R156ZZ	FR156ZZ	4.762	7.938	9.119	2.779	3.175	359	150	53	63	10	1
R166	FR166	R166ZZ	FR166ZZ	-	9.525	10.719	3.175	3.175	709	272	50	60	8	1.588
R3	FR3	R3ZZ	FR3ZZ	-	12.700	14.351	3.967	4.978	1301	488	43	53	7	2.381
R3A	-	R3AZZ	-	-	15.875	-	4.978	4.978	1480	621	38	45	8	2.381
R168	FR168	R168ZZ	FR168ZZ	6.35	9.525	10.719	3.175	3.175	373	172	48	56	11	1
R188	FR188	R188ZZ	FR188ZZ	-	12.700	13.894	3.175	4.762	1082	442	40	50	8	2
R4	FR4	R4ZZ	FR4ZZ	-	15.875	17.526	4.978	4.978	1480	621	38	45	8	2.381
R4A	-	R4AZZ	-	-	19.050	-	5.558	7.142	2336	896	36	43	6	3.5
R1810	FR1810	R1810ZZ	FR1810ZZ	7.938	12.700	13.894	3.967	3.967	542	276	40	48	12	1.2
R6	FR6	R6ZZ	FR6ZZ	9.525	22.225	24.613	5.558	7.142	3332	1422	32	38	7	3.969
R8	FR8	R8ZZ	FR8ZZ	12.7	28.575	31.12	6.35	7.938	5108	2413	27	32	8	4.762