

标准型

公称轴径 Nominal shaft diameter mm	尼龙保持架 Resin retainer		主要尺寸和公差 Major dimensions and tolerance											
	标准型 LM..UU	钢球列数 Ball circuit	Dr		D		L		B		W	D1		
			mm	公差 Tolerance μm	mm	公差 Tolerance μm	mm	公差 Tolerance μm	mm	公差 Tolerance μm				
3	LM3UU	4	3	0 -8	7	0 -9	10	0 -120	-	-	-	-		
4	LM4UU	4	4		8		12		-	-	-	-		
5	LM5UU	4	5		10		15		10.2	1.1	9.6			
6	LM6UU	4	6	0 -9	12	0 -11	19	0 -200	13.5	1.1	11.5			
8	LM8SUU	4	8		15		17		11.5	1.1	14.3			
8	LM8UU	4	8		15		24		17.5	1.1	14.3			
10	LM10UU	4	10		19		29		22	1.3	18			
12	LM12UU	4	12		21		30		23	1.3	20			
13	LM13UU	4	13		23		32		23	1.3	22			
16	LM16UU	5	16	0 -10	28	0 -13	37	0 -200	26.5	1.6	27			
20	LM20UU	5	20		32		42		30.5	1.6	30.5			
25	LM25UU	6	25		40		59		41	1.85	38			
30	LM30UU	6	30		45		64		44.5	1.85	43			
35	LM35UU	6	35		52		0 -16		70	0 -300	49.5	0 -300	2.1	49
									70		49.5		2.1	49

加长型

公称轴径 Nominal shaft diameter mm	尼龙保持架 Resin retainer		主要尺寸和公差 Major dimensions and tolerance												
	标准型 LM..UU	钢球列数 Ball circuit	Dr		D		L		B		W	D1			
			mm	公差 Tolerance μm	mm	公差 Tolerance μm	mm	公差 Tolerance μm	mm	公差 Tolerance μm					
6	LM6LUU	4	6	0 -10	12	0 -13	35	0 -300	27	0 -300	1.1	11.5			
8	LM8LUU	4	8		15		45		35		1.1	14.3			
10	LM10LUU	4	10		19		55		44		1.3	18			
12	LM12LUU	4	12		21		57		46		1.3	20			
13	LM13LUU	4	13		23		61		46		1.3	22			
16	LM16LUU	5	16		28		70		53		1.6	27			
20	LM20LUU	5	20	0 -15	32	0 -19	80	0 -400	61	0 -400	1.6	30.5			
25	LM25LUU	6	25		40		112		82		1.85	38			
30	LM30LUU	6	30		45		123		89		1.85	43			
35	LM35LUU	6	35		52		0 -19		135		0 -400	99	0 -400	2.1	49
									135			99		2.1	49